

Super Tuff Green

1

PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Super Tuff Green
Common Name: Super Tuff Green
SDS Number: Super Tuff Green
Revision Date: 10/11/2021
Chemical Formula: *** PROPRIETARY ***
Product Use: CLEANING COMPOUND, SOLVENT

Supplier Details: D.W. Davies & Co., Inc.
3200 Phillips Avenue
Racine, WI 53403

Contact: Pat Fogarty
Phone: (262) 637-6133
Fax: (262) 637-3933
Email: pfog@dwdavies.com
Web: www.dwdavies.com
Emergency: (800) 424-9300 (CHEMTREC)

2

HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Health, Serious Eye Damage/Eye Irritation, 1
Health, Skin corrosion/irritation, 1 A
Environmental, Hazards to the aquatic environment - Acute, 3
Physical, Corrosive to Metals, 1
Health, Skin corrosion/irritation, 2
Health, Serious Eye Damage/Eye Irritation, 2 A
Physical, Flammable Liquids, 4
Health, Acute toxicity, 4 Dermal
Health, Acute toxicity, 4 Inhalation
Health, Acute toxicity, 4 Oral

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: **DANGER**

GHS Hazard Pictograms:



GHS Hazard Statements:

H318 - Causes serious eye damage
H314 - Causes severe skin burns and eye damage
H402 - Harmful to aquatic life
H290 - May be corrosive to metals
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H227 - Combustible liquid
H312 - Harmful in contact with skin
H332 - Harmful if inhaled
H302 - Harmful if swallowed

GHS Precautionary Statements:

P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking
P234 - Keep only in original container.
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 - Wash _ thoroughly after handling.

Super Tuff Green

P270 - Do not eat, drink or smoke when using this product.
 P271 - Use only outdoors or in a well-ventilated area.
 P273 - Avoid release to the environment.
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P301+312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
 P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
 P302+352 - IF ON SKIN: Wash with soap and water.
 P303+361+353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P305+351+338 - IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.
 P310 - Immediately call a POISON CENTER or doctor/physician.
 P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
 P321 - Specific treatment (see _ on this label).
 P322 - Specific measures (see _ on this label).
 P330 - Rinse mouth.
 P332+313 - If skin irritation occurs: Get medical advice/attention.
 P337+313 - Get medical advice/attention.
 P362 - Take off contaminated clothing and wash before reuse.
 P363 - Wash contaminated clothing before reuse.
 P370+378 - In case of fire: Use _ for extinction.
 P390 - Absorb spillage to prevent material damage.
 P403+235 - Store in a well ventilated place. Keep cool.
 P405 - Store locked up.
 P406 - Store in a corrosive resistant/_ container with a resistant inner liner.
 P501 - Dispose of contents/container to _

Hazards not Otherwise Classified (HNOC) or not Covered by GHS

Route of Entry: Eyes; Ingestion; Skin;
Target Organs: Digestive tract;
Skin Contact: May cause irritation.
Eye Contact: May cause irritation.
Ingestion: May cause irritation to digestive tract

3 COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Ingredients		
CAS#	%	Chemical Name
111-76-2	<5.50%	2-Butoxyethanol
1310-58-3	<1.50%	Potassium hydroxide (K(OH))

4 FIRST AID MEASURES

Inhalation: Not a direct hazard.
Skin Contact: Wash with soap and water.
Eye Contact: Flush with large amounts of water. Consult a Physician
Ingestion: Drink large quantities of water. Rinse mouth with water. Seek immediate medical attention

5 FIRE FIGHTING MEASURES

Flash Point: 200 F
Flash Point Method: Closed Cup

Wear self contained breathing apparatus and other protective clothing.

6 ACCIDENTAL RELEASE MEASURES

Super Tuff Green

Avoid contact with eyes.

Ventilate area and wash spill site after material pickup is complete.

7**HANDLING AND STORAGE**

Handling Precautions: Avoid contact with eyes, skin, or clothing. Consider normal working hygiene.
Storage Requirements: Store in cool/dry area.

8**EXPOSURE CONTROLS/PERSONAL PROTECTION****Personal Protective Equipment:**

2-Butoxyethanol (111-76-2) [<5.50%]

Personal protective equipment

Eye/face protection: Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching gloves outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact: Material: Nitrile rubber Minimum layer thickness: 0.4 mm Break through time: 480 min
Material tested: Camatril (KCL 730 / Aldrich Z677442, Size M)

Splash contact: Material: Nitrile rubber Minimum layer thickness: 0.2 mm Break through time: 30 min
Material tested: Dermatril P (KCL 743 / Aldrich Z677388, Size M) data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374 If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection: Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection: Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi- purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure: Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Potassium hydroxide (K(OH)) (1310-58-3) [<1.50%]

Personal protective equipment

Eye/face protection: Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching gloves outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact: Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min

Super Tuff Green

Material tested: Dermatril (KCL 740 / Aldrich Z677272, Size M)

Splash contact: Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min
Material tested: Dermatril (KCL 740 / Aldrich Z677272, Size M) data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374 If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection: Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection: Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure: Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

2-Butoxyethanol (111-76-2) [$<5.50\%$]

Components with workplace control parameters

TWA 20 ppm USA. ACGIH Threshold Limit Values (TLV)

Eye & Upper Respiratory Tract irritation

Confirmed animal carcinogen with unknown relevance to humans

TWA 5 ppm USA. NIOSH Recommended Exposure Limits
24 mg/m³

Potential for dermal absorption

TWA 50 ppm USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
240 mg/m³

Skin designation

The value in mg/m³ is approximate.

TWA 25 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
120 mg/m³

Skin notation

Potassium hydroxide (K(OH)) (1310-58-3) [$<1.50\%$]

Components with workplace control parameters

C 2 mg/m³ USA. ACGIH Threshold Limit Values (TLV)

Eye, skin, & Upper Respiratory Tract irritation

C 2 mg/m³ USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000

Super Tuff Green

C 2 mg/m³ USA. NIOSH Recommended
Exposure Limits

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Colorless liquid.	Odor:	Slight Solvent Smell
Physical State:	Liquid	Solubility:	Complete
Spec Grav./Density:	1.0	Flash Point:	200 F
Boiling Point:	212 F	Vapor Density:	~1
Vapor Pressure:	~25 mm Hg @ 68F	Bulk Density:	1.1
Evap. Rate:	<Ether		

10 STABILITY AND REACTIVITY

Reactivity:	Stable, non reactive
Chemical Stability:	Product is stable under normal conditions.
Conditions to Avoid:	Oxidation promoting conditions (Heat, Sunlight and Air).
Materials to Avoid:	Strong Acids; Strong Oxidizing Agents.
Hazardous Decomposition:	Carbon Oxides, Aldehydes, Aromatic and other Hydrocarbons
Hazardous Polymerization:	Will not occur.

11 TOXICOLOGICAL INFORMATION

2-Butoxyethanol (111-76-2) [<5.50%]

Information on toxicological effects

Acute toxicity:

LD50 Oral - rat - 470 mg/kg

LC50 Inhalation - rat - 4 h - 450 ppm Remarks: Behavioral:Ataxia. Nutritional and Gross Metabolic:Weight loss or decreased weight gain.

LD50 Dermal - rabbit - 220 mg/kg

LD50 Intraperitoneal - rat - 220 mg/kg

LD50 Intravenous - rat - 307 mg/kg

Skin corrosion/irritation: Skin - rabbit Result: Open irritation test

Serious eye damage/eye irritation: Eyes - rabbit Result: Moderate eye irritation - 24 h

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (2-Butoxyethanol)

Super Tuff Green

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Overexposure may cause reproductive disorder(s) based on tests with laboratory animals.

Specific target organ toxicity - single exposure: no data available

Specific target organ toxicity - repeated exposure: no data available

Aspiration hazard: no data available

Additional Information:

RTECS: KJ8575000

Human exposure above 200 ppm can be expected to cause narcosis, damage to the kidney and liver and present an abnormal blood picture showing erythropenia, reticulocytosis, granulocytosis, leukocytosis, and would be likely to

cause fragility of erythrocytes and hematuria. Swallowing of 2-butoxyethanol results in a sour taste that turns to a burning sensation and is followed by numbness of the tongue which indicates paralysis of the sensory nerve endings., Central nervous system depression, Headache, narcosis

Stomach - Irregularities - Based on Human Evidence

Potassium hydroxide (K(OH)) (1310-58-3) [$<1.50\%$]

Information on toxicological effects

Acute toxicity:

LD50 Oral - rat - 333 mg/kg

Inhalation: no data available

Dermal: no data available

Skin corrosion/irritation: Skin - rabbit Result: Severe skin irritation - 24 h

Serious eye damage/eye irritation: Eyes - rabbit Result: Corrosive to eyes (OECD Test Guideline 405)

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential

Super Tuff Green

carcinogen by OSHA.

Reproductive toxicity: no data available

Specific target organ toxicity - single exposure: no data available

Specific target organ toxicity - repeated exposure: no data available

Aspiration hazard: no data available

Additional Information:

RTECS: TT2100000

12**ECOLOGICAL INFORMATION**

2-Butoxyethanol (111-76-2) [<5.50%]

Information on ecological effects

Toxicity:

Toxicity to fish LC50 - other fish - 220 mg/l - 96 h.

Toxicity to daphnia and EC50 - Daphnia magna (Water flea) - 1,815 mg/l - 24 h.

other aquatic invertebrates

Persistence and degradability: no data available

Ratio BOD/ThBOD 88 %

Bioaccumulative potential: no data available

Super Tuff Green

Mobility in soil: no data available

Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects: no data available

Potassium hydroxide (K(OH)) (1310-58-3) [<1.50%]

Information on ecological effects

Toxicity:

Toxicity to fish LC50 - *Gambusia affinis* (Mosquito fish) - 80 mg/l - 96 h.

Persistence and degradability: The methods for determining the biological degradability are not applicable to inorganic substances.

Bioaccumulative potential: no data available

Mobility in soil: no data available

Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life.

no data available

Super Tuff Green

2-Butoxyethanol (111-76-2) [$<5.50\%$]

Waste treatment methods

Product: This combustible material may be burned in a chemical incinerator equipped with an afterburner and scrubber. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging: Dispose of as unused product.

Potassium hydroxide (K(OH)) (1310-58-3) [$<1.50\%$]

Waste treatment methods

Product: Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

Contaminated packaging: Dispose of as unused product.

14 TRANSPORT INFORMATION

ID8000, Consumer commodity, 9

15 REGULATORY INFORMATION

Component (CAS#) [%] - CODES

2-Butoxyethanol (111-76-2) [$<5.50\%$] HAP, MASS, OSHAWAC, PA, TSCA, TXAIR

RQ(1000LBS), Potassium hydroxide (K(OH)) (1310-58-3) [$<1.50\%$] CERCLA, CSWHS, MASS, OSHAWAC, PA, TSCA, TXAIR

Regulatory CODE Descriptions

RQ = Reportable Quantity
HAP = Hazardous Air Pollutants
MASS = MA Massachusetts Hazardous Substances List
OSHAWAC = OSHA workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
TSCA = Toxic Substances Control Act
TXAIR = TX Air Contaminants with Health Effects Screening Level
CERCLA = Superfund clean up substance
CSWHS = Clean Water Act Hazardous substances




16 OTHER INFORMATION

Super Tuff Green

NFPA: Health = 2, Fire = 1, Reactivity = 0, Specific Hazard = n/a

HMIS III: Health = 2, Fire = 1, Physical Hazard = 0

HMIS PPE: B - Safety Glasses, Gloves



D.W. Davies & Co., Inc. makes no representations or warranties, either express or implied, including without limitation any warranties of merchantability, fitness for a particular purpose with respect to the information set forth herein or the product to which the information refers.